

DATASHEET

Modbus RTU or Modbus TCP/IP to JCI Metasys N2 QuickServer Gateways PS-QS-1x10-0117

The QuickServer line of communication gateways are designed to link building automation driven networks with industrial control networks. The QuickServer gateways are available with limits of up to 250 or 500 points of application data. Custom configuration services are also available for the QuickServer gateways. The user will be asked to fill out a worksheet, and answer some basic questions pertaining to the application, and a custom configuration will be provided along with the unit, reducing time to commission.



Specifications

Field Connections

- Ethernet 10/100 RJ45
- Two Serial RS-485 terminal (up to 115K baud)

Environment

- Operating temperature: -40°F to 167°F (-40°C to 75°C)
- Relative humidity: 5% to 90% RH, with no condensation

Power Requirements

- 9 to 30 Vdc or Vac or 5 Vdc
- Current draw 240mA @ 12V

Other

- Configuration/Diagnostic utilities
- Capacity: 250 or 500 Points
- Table, Wall or DIN rail mount

Physical Dimensions (WxDxH)

- 4.5 x 3.2 x 1.6 in. (11.5 x 8.3 x 4.1 cm)
- 0.4 lbs (0.2 Kg)

Approvals

- TUV approved to UL 916 standard
- CE Mark
- BTL Mark (PS-QS-1010)
- RoHS Compliant
- FCC Part 15 Compliant

Ordering Information

To order this product, please use the following:

- PS-QS-1010-0117** 250 Points
- PS-QS-1510-0117** 500 Points

How to Contact Us: Sales and Support

Sales and Technical Support for this product are provided by ProSoft Technology. Contact our worldwide Sales or Technical Support teams directly by phone or email:

Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com

Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, Europe@prosoft-technology.com

North America

+1.661.716.5100, support@prosoft-technology.com

Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com

LonWorks[®] is a trademark of Echelon Corporation
Metasys[®] is a trademark of Johnson Controls
BACnet[®] is a trademark of ASHRAE