



RadioLinX Industrial Frequency Hopping Ethernet

RLX-FHE

The RadioLinX Frequency Hopping Ethernet radio is designed to operate in high-interference environments by combining advanced frequency hopping and digital signal processing technology with outstanding receiver sensitivity and antenna diversity. This combination results in exceptional noise and interference rejection.

The RLX-FHE is compatible with all protocols that run over standard IEEE 802.3 Ethernet including TCP/IP, UDP, IPX, NetBEUI, BootP, EtherNet/IP, and Modbus/TCP. The RLX-FHE simultaneously supports multiple 802.3 compliant protocols.

Features and Benefits

- Supports up to 1000 addressed devices with 2000 radios and 78 repeaters per network
- 64 user-selectable data channels for multiple network operation
- Active antenna diversity
- 2.4 GHz frequency hopping spread spectrum (FHSS) technology
- Secure wireless communications with data encryption, proprietary radio protocol, and 2.4 GHz FHSS physical layer
- Industrial temperature range
- 15+ (24 km) mile range with high-gain antennas (longer with repeaters)
- Remote diagnostics without interrupting data communications
- Over air user programmability (after initial configuration) using Windows-based software
- Three year standard warranty

Specifications

Radio	
Frequency	2400 to 2483.5 MHz (varies by country)
Compliance	IEEE 802.3, 802.3u, 802.3x
Protocols	All standard IEEE 802.3 protocols
Encryption	ARC4 (40 or 128 bit)
Network Topology	Peer-to-Peer, store and forward repeater
Hop Patterns	64 independent, non-interfacing networks
Error Detection	32-bit CRC and ARQ (Automatic Re-Send Query)
Radio Type	Frequency Hopping Spread Spectrum
Output power	1mW to 250mW, programmable (varies by country)
Channel data rates	250 Kbps
Receiver sensitivity	-96 dBm @ 10 ⁻⁶ BER
Channels - user selectable	64 North America (varies by country)

RadioLinX Frequency Hopping Ethernet

RLX-FHE

Use the RLX-FHE in applications where high-power/long-range, secure, high-speed, un-tethered 2.4 GHz Frequency Hopping Ethernet connectivity is required.

- Connect to moving or remote industrial devices
- Combine voice, video and data on a single, high speed industrial wireless network
- Use for applications generating many packets per second or with high aggregate data requirements such as I/O messaging and client/server based HMI

How to Contact Us: Sales and Support

All ProSoft Technology® products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com
Languages spoken include: Chinese, Japanese, English

Europe - Middle East - Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com
Languages spoken include: French, English

North America

+1.661.716.5100, support@prosoft-technology.com
Languages spoken include: English, Spanish

Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com
Languages spoken include: Spanish, English

Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com
Languages spoken include: Portuguese, English

Radio	
Typical indoor range	500 to 1500 ft (150 to 450 meters)
Outdoor range	15 + miles line of sight with high-gain antennas
Security	ARC4 (40 or 128 bit)

Physical	
Enclosure	Extruded aluminum with DIN and panel mount
Size	4.10 in. x 3.71 in. x 2.05 in. (104.1 mm x 94.23 mm x 52.07 mm)
Vibration	IEC 60068-2-6
Shock	IEC 60068-2-27
Ethernet port	10/100 Base-T connector, shielded RJ45 IEEE 802.3, 802.3u, 802.3x

Antenna Ports	Two RP-SMA connectors, automatic antenna diversity
Weight	1 lbs /454g

Environmental	
Operating temperature	-40°C to +70°C (-40°F to 158°F)
Humidity	To 90% RH, non-condensing
External power	10 to 24 VDC
Average power	< 4W

Regulatory Approvals

Type Approvals	
FCC	FCC Part 15.247
Industry Canada	RSS 210
Europe / CE	LVD EN 50850-2000 RF Safety EN 50364-2001 EMC EN 301 489-1, EN 301 489-17 Spectrum EN 300 328 v1.4.1
Mexico	Nom 121 SCT1 2 or 1
Australia	AS/NZS 4771
Brazil	365 / 2004 e 238 / 2000
Malaysia	SIRIM

Hazardous Locations	
UL	UL 1604 Class 1 Division 2, Groups A, B, C, D Temp Code T4A
CSA/cUL	C22.2 No. 213-1987
ATEX Zone 2	ATEX II 3 G EEx nC IIC

Visit our web site for the latest certification information.

Additional Products

ProSoft Technology® offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

Ordering Information

Use the following Ordering Information to identify the radio product needed for your region. If you are unsure which radio to select, please contact your local distributor.

RadioLinx 2.4 GHz Frequency Hopping Radios

Country	Catalog #	Frequency	RF Power	Pwr Sply
Australia	RLX-FHE-AU	2400 to 2483.5 MHz	4W	AU
Brazil	RLX-FHE-US	2400 to 2483.5 MHz	4W	US
China	RLX-FHE-CN	2400 to 2483.5 MHz	500 mW EIRP	EU
Europe	RLX-FHE-EU	2400 to 2483.5 MHz	100 mW EIRP	EU
France	RLX-FHE-FR	2400 to 2454 MHz	100 mW EIRP	EU
India	RLX-FHE-UK	2400 to 2483.5 MHz	4 W EIRP @ 6dBi antenna gain	UK
Malaysia	RLX-FHE-UK	2400 to 2483.5 MHz	100 mW EIRP	UK
Mexico	RLX-FHE-MX	2450 to 2483.5 MHz	650 mW EIRP	US
Saudi Arabia	RLX-FHE-SA	2413 to 2439 MHz	100 mW EIRP	US
Singapore	RLX-FHE-SG	2400 to 2483.5 MHz	100 mW EIRP	UK
South Africa	RLX-FHE-EU	2400 to 2483.5 MHz	100 mW EIRP	EU
South Korea	RLX-FHE-EU	2400 to 2483.5 MHz	100 mW EIRP	EU
United Kingdom	RLX-FHE-UK	2400 to 2483.5 MHz	100 mW EIRP	UK
USA	RLX-FHE-US	2400 to 2483.5 MHz	4W	US
Venezuela	RLX-FHE-VE	2400 to 2483.5 MHz	4W	US

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, go to <http://www.prosoft-technology.com>

Distributors:

Place your order by email or fax to:

North American / Latin American / Asia Pacific

orders@prosoft-technology.com,
fax to +1 661.716.5101

Europe

europe@prosoft-technology.com,
fax to +33 (0) 5.61.78.40.52