

## DATASHEET

### EtherNet/IP or DF1 to LonWorks QuickServer Gateways PS-QS-1x11-0783

The QuickServer line of communication gateways are designed to link building automation networks using LonWorks communication with industrial control networks utilizing Ethernet/IP or DF1 communications. The QuickServer gateways are available with limits of up to 250 or 500 points of application data.



### Specifications

#### Field Connections

- Ethernet 10/100 RJ45
- Serial RS-485 terminal (up to 115K baud)
- FTT-10 LonWorks port

#### Environment

- Operating temperature: -40°F to 167°F (-40°C to 75°C)
- Relative humidity: 5% to 90% RH, with no condensation

#### Power Requirements

- 9 to 30 VDC or 12 to 24 VAC
- Current draw 250mA @ 12Vdc

#### Other

- Configuration/Diagnostic utilities
- Capacity: 250 or 500 Points
- Table, Wall or DIN rail mount

#### Physical Dimensions (W x D x H)

- 4.5 x 3.2 x 1.6 in. (11.5 x 8.3 x 4.1 cm)
- 0.4 lbs (0.2 Kg)

#### Approvals

Please visit our website: [www.prosoft-technology.com](http://www.prosoft-technology.com)

### Ordering Information

To order this product, please use the following:

<b>PS-QS-1011-0783</b>	250 Points
<b>PS-QS-1511-0783</b>	500 Points

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, please visit:

[www.prosoft-technology.com](http://www.prosoft-technology.com) and select *Where to Buy*.

LonWorks<sup>®</sup> is a trademark of Echelon Corporation

Metasys<sup>®</sup> is a trademark of Johnson Controls

BACnet<sup>®</sup> is a trademark of ASHRAE