



DNP 3.0 Master to PROFIBUS DP Master Gateway

5204-DNPM-PDPM

The DNPM-PDPM modules are the ideal solution for the many applications where DNP 3.0 Master connectivity can be used to integrate a PROFIBUS DP Master device into a system. The DNP 3.0 Master gateway is a powerful module designed with Server support, enabling easy connection to Rockwell Automation PLCs (CLX, SLC, PLC, CPLX, and similar devices). In combination with the PROFIBUS device support, the module provides a very powerful interface to the many PROFIBUS devices which are in use in the industrial marketplace today. Applications for the module are found in most industries, especially Manufacturing, Oil and Gas, Electrical Power and Food Processing.

How to Contact Us: Sales and Support

All ProSoft Technology® products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com
Languages spoken include: Chinese, Japanese, English

Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com
Languages spoken include: French, English

North America

+1.661.716.5100, support@prosoft-technology.com
Languages spoken include: English, Spanish

Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com
Languages spoken include: Spanish, English

Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com
Languages spoken include: Portuguese, English

DNP 3.0 Master to PROFIBUS DP Master Gateway

5105-DNPM-PDPM

The ProLinx DNP 3.0 Master to PROFIBUS DP Master creates a powerful connection between devices on a DNP 3.0 network and PROFIBUS DP slave devices. This stand-alone DIN-rail mounted protocol gateway provides one serial port and PROFIBUS DB Slave port.

The DNP 3.0 Master protocol driver supports Master implementations of the protocol on one port. This port is fully configurable.

The PROFIBUS DP Master protocol driver supports Master implementations of the protocol on either a Mono-Master or Multi-Master network.

DNP 3.0 Master

The DNP 3.0 Master driver provides extensive support for Master implementations of the protocol. The serial port on the gateway is user-configurable to support the DNP 3.0 protocol (Master, Baud Rate, etc).

General Parameters

Internal Database	Binary Inputs: 0 to 500 word count Analog Inputs: 0 to 500 points Counters: 0 to 250 points Binary Outputs: 0 to 500 word count Analog Outputs: 0 to 500 points
DNP Mode	DNP 3.0 Master – Level 2
DNP Object Support	DNPM Driver Manual contains full Object Definition documentation

DNP Master

Node address	0 to 65534 – software selectable
Slave count	Up to 40 slave devices
Command count	Up to 300 user defined commands to interface with remote slave devices

PROFIBUS DP Master

The PROFIBUS Master protocol driver exists as a single port implementation. The driver can be configured as a Class 1 PROFIBUS Master to continuously interface with other PROFIBUS slave devices. The unit is also used for configuration of the nodes on the PROFIBUS network. It provides access to both standard as well as extended diagnostic information.

General Parameters

Communication parameters Baud Rate: 9.6 kbit/s – 12 Mbit/s

PROFIBUS Master

Command List Read Diag
Global Cmd
Read Cntrs
Reset Cntrs

Node address 0 - 125 – software selectable.

Status Data Error codes, counters and port status available per configured slave on the network.

General Specifications

The ProLinx Communication Modules provide connectivity for two or more dissimilar network types. The modules, encased in sturdy extruded aluminum, are stand-alone DIN-rail mounted protocol gateways, providing communication between many of the most widely used protocols in industrial automation today.

Hardware Specifications

Specification	Description
Power Supply	24 VDC nominal 18 to 36 VDC allowed Positive, Negative, GND Terminals 2.5 mm screwdriver blade
Current Load	500 mA max@ 24 VDC
Operating Temperature	-20 to 50°C (-4 to 122°F)
Storage Temperature	-40 to 85°C (-40 to 185°F)
Relative Humidity	5 to 95% (non-condensing)
Dimensions	Standard: 5.20H x 2.07W x 4.52D in. (13.2cmH x 5.25cmW x 11.48cmD) Extended: 5.20H x 2.73W x 4.52D in. (13.2cmH x 6.934cmW x 11.48cmD)
LED Indicators	Power and Module Status Application Status Serial Port Activity LED Serial Activity and Error LED Status
Configuration Serial Port	DB-9M RS-232 only No hardware handshaking
Ethernet Port (Ethernet modules only)	RJ45 Connector Link and Activity LED indicators
Application Serial Ports	RS-232/422/485 RS-232 handshaking configurable RS-422/485 screw termination included
Serial Port Isolation	2500V RMS port signal isolation per UL 1577 3000V DC min. port to ground and port to logic power isolation

Specification

Description

Shipped with Each Unit Mini-DIN to DB-9M serial cables
4 ft RS-232 configuration cable
2.5mm screwdriver
CD (docs and Configuration utility)
RS-422/485 DB-9 to Screw Terminal Adaptor (1 or 4, depending on ports)

ProSoft Configuration Builder

ProSoft Configuration Builder (PCB) provides a quick and easy way to manage module configuration files customized to meet your application needs. PCB is not only a powerful solution for new configuration files, but also allows you to import information from previously installed (known working) configurations to new projects.

Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

Ordering Information

To order this product, please use the following:

5204-DNPM-PDPM DNP 3.0 Master to PROFIBUS DP Master Gateway

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

Distributors:

Place your order by email or fax to:

North American / Latin American / Asia Pacific
orders@prosoft-technology.com,
fax to +1 661.716.5101

Europe

europe@prosoft-technology.com,
fax to +33 (0) 5.61.78.40.52

Copyright © ProSoft Technology, Inc. 2000 - 2007. All Rights Reserved.
May 03, 2007