

DATASHEET

EtherNet/IP, BACnet/IP, and BACnet MS/TP QuickServer Gateways PS-QS-1x10-0780

The QuickServer line of communication gateways are designed to link building automation driven networks with industrial control networks.

The PS-QS-1x10-0780 simultaneously supports EtherNet/IP, BACnet/IP, and BACnet MS/TP, allowing for any combination of protocols to be used. The QuickServer gateways are available with limits of 250 or 500 points of application data.



Specifications

Field Connections

- Ethernet 10/100 RJ45
- Two Serial RS-485 terminal (up to 115K baud)

Environment

- Operating temperature: -40°F to 167°F (-40°C to 75°C)
- Relative humidity: 5% to 90% RH, with no condensation

Power Requirements

- 9 to 30 Vdc or Vac or 5 Vdc
- Current draw 240mA @ 12V

Other

- Configuration/Diagnostic utilities
- Capacity: 250 or 500 Points
- Table, Wall or DIN rail mount

Physical Dimensions (W x D x H)

- 4.5 x 3.2 x 1.6 in. (11.5 x 8.3 x 4.1 cm)
- 0.4 lbs (0.2 Kg)

Approvals

Please visit our website: www.prosoft-technology.com

Ordering Information

To order this product, please use the following:

PS-QS-1010-0780	250 Points
PS-QS-1510-0780	500 Points

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, go to: www.prosoft-technology.com and select *Where to Buy*.

LonWorks[®] is a trademark of Echelon Corporation
Metasys[®] is a trademark of Johnson Controls
BACnet[®] is a trademark of ASHRAE