

General Specifications

- ◆ Single-slot, 1769 backplane-compatible
- ◆ The module is recognized by the processor as an Input/Output module.
- ◆ The included sample ladder logic file is used for data transfer between module and processor.
- ◆ Configuration data can be downloaded over Modbus or delivered by user-defined ladder.
- ◆ Supports CompactLogix and MicroLogix 1500 LRP Controllers except 1769-L23E-QBFC1B, 1769-L16x, and 1769-L18x

Functional Specifications

The AFC module operates as a powerful flow computer module, augmenting the operation of the CompactLogix[®] processor by providing a dedicated and accurate set of flow calculations.

- ◆ Calculates flow rates, accumulated volumes, accumulated mass, and accumulated energy
- ◆ Calculation results are transferred to processor memory and may also be transferred to a SCADA host using Modbus.
- ◆ User configurable, allowing each of the meter runs to be individually set up to meet the specific requirements of an application

Archiving

- ◆ Supports data archiving and event logging
- ◆ Data archiving is available for each meter run, hourly for two days (48 records) and daily for one month (35 records) under default configuration, with optional extended archives up to 1,440 hourly (60 days) and 1,440 daily. The actual number of archives is dependent upon the size set by the user for each archive type.
- ◆ Event logging feature provides storage of up to 1,999 station events.

Configurable Options

- ◆ User-selectable units for totalizers and flow rates on a per channel basis
- ◆ Roll-over value for resettable and non-resettable totalizers for every meter channel
- ◆ Process analog input units and ranges (pressure, temperature, differential pressure, density) from analog input modules and pulse inputs from pulse/frequency input modules in a CompactLogix chassis
- ◆ Fluid selection provides a choice of several liquid groups or gas measurement, using AGA or ISO calculations.
- ◆ Event log reports for all security-sensitive configuration data (for example, orifice diameter) are date and time stamped. This data can be saved to disk for importing into any spreadsheet or printed as a hard copy

Modbus Interface

- ◆ All three Modbus slave ports allow for SCADA communication and can be configured for RTU or ASCII mode.
- ◆ Modbus table may be re-mapped as a virtual Modbus slave for user-assigned contiguous register polling by a SCADA master (up to 20,000 registers).
- ◆ One of the three ports can be configured as a Modbus Master port to poll data from remote devices.

System Requirements - AFC Manager

This configuration software is designed for Microsoft Windows 98/NT/2000/XP/Vista/7. Minimum hardware requirements for a Windows 98 system are as listed below. More advanced operating systems have significantly higher minimum requirements regardless of AFC Manager minimum requirements.

- ◆ 100 MHz or faster Pentium PC
- ◆ 128 MB RAM
- ◆ DVD drive
- ◆ 100 MB available hard drive space
- ◆ Available RS-232 serial port and null modem cable



Additional Products

ProSoft Technology[®] offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms. For a complete list of products, visit our web site at: www.prosoft-technology.com

Ordering Information

To order this product, please use the following:

Liquid and Gas Flow Computer for CompactLogix[®]

MVI69-AFC

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, go to: www.prosoft-technology.com and select *Where to Buy* from the menu.

Measurement Compliance Standards

- ◆ API MPMS Chapter 14.3 (AGA Report No. 3), 1992 ed.
- ◆ ISO 5167, Part 2, 2003 ed.
- ◆ AGA Report No. 7
- ◆ API MPMS Chapter 14.2 (AGA Report No. 8), 1992 ed., Detail Characterization Method (for compressibilities and densities) and Appendix C.3 (for energy content)
- ◆ API MPMS Chapter 14.9 (AGA Report No. 11) (Coriolis mass meters)
- ◆ AGA Report No. 9 (Ultrasonic meters)
- ◆ API MPMS Chapter 11.1, 2004 ed. (complete)
- ◆ API MPMS Chapter 11.2 (CPL for lower-density liquids)
- ◆ GPA Technical Paper 27 (CTL and density correction for lower-density liquids)
- ◆ GPA Technical Paper 15 (vapour pressure for lower-density liquids)
- ◆ API MPMS Chapter 12.2 (excluding provers)
- ◆ API MPMS Chapter 20.1 (measurement of liquids with high water content)
- ◆ API MPMS Chapter 21.1 (gases)
- ◆ API MPMS Chapter 21.2 (liquids)
- ◆ GPA 2145-03
- ◆ GPSA Engineering Data Book (SI)
- ◆ GPSA Engineering Data Book (FPS)

Hardware Specifications

| Specification | Description |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions | Standard 1769 Single-slot module |
| Current Load | 800 mA max @ 5 VDC Power supply distance rating of 2 (L43 and L45 installations on first 2 slots of 1769 bus) |
| Operating Temp. | 32°F to 140°F (0°C to 60°C) |
| Storage Temp. | -40°F to 185°F (-40°C to 85°C) |
| Relative Humidity | 5% to 95% RH, with no condensation |
| LED Indicators | Battery and Module Status Application Status Serial Port Activity CFG Port Activity |
| CFG Port (CFG) | RJ45 (DB-9F with supplied cable) RS-232 only No hardware handshaking |
| App Ports (P1,P2) (Serial modules) | RS-232, RS-485 or RS-422 (jumper selectable) RJ45 (DB-9F with supplied cable) RS-232 handshaking configurable 500V Optical isolation from backplane |
| Shipped with Unit | RJ45 to DB-9M cables for each port 6-foot RS-232 configuration cable |

Agency Approvals and Certifications

Please visit our website: www.prosoft-technology.com



Where Automation
Connects™

Global Distribution

We think like you do

ProSoft Technology® products are distributed and supported worldwide through a network of over 500 distributors in over 50 countries. Our knowledgeable distributors are familiar with your application needs. For a complete list of distributors, go to our web site at:

www.prosoft-technology.com

Global Support

We are there for you

All ProSoft Technology products are backed with free, unlimited technical support. Contact our worldwide Technical Support team directly by phone or email.

Global Offices

We are where you are

ProSoft Technology has regional offices worldwide available to help you with all your industrial application needs. If you need help choosing a ProSoft Technology solution for your particular application check out our contact information under distributor sales on the web site at:

www.prosoft-technology.com