

DATASHEET

5 GHz Terminated Radiating Cable RCH50-50-xxxM

The ProSoft Technology RCH50-50-xxxM Radiating Cable is specially designed to radiate 802.11a and 802.11n RF signals operating in the spread spectrum 5 GHz band.

Acting as a long, flexible antenna, the Radiating Cable may be installed along monorail systems, overhead cranes and through tunnels to propagate wireless data signals in situations tough for traditional antenna systems

The cable is pre-terminated with N-Female connectors saving time during installation. It also includes the proper number and type of hangers to facilitate your installation. It is available in multiple lengths to meet the needs of your application.

Specially tested with ProSoft Technology 802.11 Fast Industrial Hotspots utilizing Fast Roam Technology, the Radiating Cable product line offers reliable and flexible options in challenging RF environments.



Features

- ◆ Special coaxial shield design uses slots to radiate RF signals which acts like a long, flexible antenna to solve challenging RF situations
- ◆ Supports 5 GHz RF band wireless technologies, optimized for 802.11a and 802.11n wireless LAN systems
- ◆ Pre-terminated with N female connector(s) to save time during installation
- ◆ Includes the proper number and type of hangers for easy installation
- ◆ Halogen-free low smoke flame retardant jacket meets most fire code requirements (check with local regulations)

Specifications

RCH Terminated Cable

Size	1.27 cm (0.5 in)
Frequency Range	5 GHz to 6 GHz
Connectors	Two (2) N-Female jack
Jacket	Halogen-free low smoke flame retardant
Slot Design	Groups of slots at short intervals
Indication of Slot Alignment	Sheath Marking (180°)
Impedance	50 Ohm
Typical Attenuation	
5 GHz	22 dB/100 m (6.86 dB/100 ft)
5.85 GHz	24 dB/100 m (7.3 dB/100 ft)
Velocity Ratio	88%
Capacitance	76 pF/meter
Dielectric Material	Cellular polyethylene
Diameter Inner Conductor	4.8 mm (0.19 in)
Diameter Dielectric	12.4 mm (0.49 in)
Diameter over Jacket	15.5 mm (0.61 in)
Minimum Bending Radius (single bend)	200 mm (7.87 in)
Recommended Hanger/Clamp Interval	One per meter (3.3 ft)
Storage Temperature	-70 to +85°C (-94 to +185°F)
Installation Temperature	-25 to +60°C (-13 to +140°F)
Operating Temperature	-40 to +85°C (-40 to +185°F)

Ordering Information

Please contact ProSoft Technology Support to order this product:

Internet	Web Site: www.prosoft-technology.com/support E-mail address: support@prosoft-technology.com
Asia Pacific (location in Malaysia)	Tel: +603.7724.2080, E-mail: asiapc@prosoft-technology.com Languages spoken include: Chinese, English
Asia Pacific (location in China)	Tel: +86.21.5187.7337 x888, E-mail: asiapc@prosoft-technology.com Languages spoken include: Chinese, English
Europe (location in Toulouse, France)	Tel: +33 (0) 5.34.36.87.20, E-mail: support.EMEA@prosoft-technology.com Languages spoken include: French, English
Europe (location in Dubai, UAE)	Tel: +971-4-214-6911, E-mail: mea@prosoft-technology.com Languages spoken include: English, Hindi
North America (location in California)	Tel: +1.661.716.5100, E-mail: support@prosoft-technology.com Languages spoken include: English, Spanish
Latin America (Oficina Regional)	Tel: +1-281-2989109, E-Mail: latinam@prosoft-technology.com Languages spoken include: Spanish, English
Latin America (location in Puebla, Mexico)	Tel: +52-222-3-99-6565, E-mail: soporte@prosoft-technology.com Languages spoken include: Spanish
Brasil (location in Sao Paulo)	Tel: +55-11-5083-3776, E-mail: brasil@prosoft-technology.com Languages spoken include: Portuguese, English



Where Automation Connects™ Global Distribution

ProSoft Technology® products are distributed and supported worldwide through a network of over 500 distributors in over 50 countries. Our knowledgeable distributors are familiar with your application needs. For a complete list of distributors, go to our web site at:

www.prosoft-technology.com

Ordering Information

To order this product, please contact ProSoft Technology Support for assistance.

Copyright © 2014 ProSoft Technology, Inc., all rights reserved. 2/14/2014

Specifications subject to change without notice.